

Appln. No. 10/721,658  
Filed: November 25, 2003  
Reply to Office action mailed September 25, 2007  
Response filed November 27, 2007

**LISTING OF CLAIMS:**

The following listing of claims replaces all previous versions, and listings, of claims in the Application.

Claim 1. (Previously presented) A system for generating difference information between a first binary image of an electronic device and a second binary image of the electronic device, the system comprising:

a bank order determination unit adapted to employ at least one differential evolution technique to determine a bank order of updating electronic device memory comprising a plurality of banks; and

wherein the determined bank order and the difference information are transmitted to and processed by the electronic device to update memory in the electronic device.

Claim 2. (Original) The system according to claim 1, wherein the first binary image and the second binary image comprise at least one of firmware and software in memory banks of the electronic device and the bank order determination unit being adapted to employ genomes to represent bank orders of memory banks of the electronic device.

Claim 3. (Previously presented) The system according to claim 2, wherein the bank order determination unit is also adapted to employ genomes to represent other additional parameters, wherein the system is also adapted to determine optimum values for the bank order and other additional parameters employing the at least one differential evolution technique, and wherein optimum values for the bank order and other additional parameters make the update package compact to the greatest degree attainable by the system.

Claim 4. (Previously presented) The system according to claim 3, wherein the other additional parameters are selected from instructions associated with at least one

Appln. No. 10/721,658  
Filed: November 25, 2003  
Reply to Office action mailed September 25, 2007  
Response filed November 27, 2007

of run-length encoding (RLE) instructions, copy (CPY) instructions, and duplicate (DUP) instructions.

Claim 5. (Original) The system according to claim 4, further comprising an evolve population module adapted to evolve a population of genomes by at least one generation, wherein the evolve population module is also adapted to evaluate the population and sort the population before evolving the population to subsequent generations, and the evolve population module is adapted to selectively create crossover genomes as part of an evolution process and store the crossover genomes for subsequent processing.

Claim 6. (Previously presented) A method for generating an update package comprising difference information for updating at least one of firmware and software in memory of an electronic device, the memory comprising a plurality of banks, the method comprising:

determining a bank order for processing images of the memory during generation of difference information, using at least one differential evolution technique; and  
employing the bank order to generate the update package.

Claim 7. (Previously presented) The method according to claim 6, wherein the bank order comprises an optimal bank order that make the update package compact to the greatest degree attainable by the method, and wherein determining an optimal bank order further comprises employing at least one genetic computation technique, wherein the at least one genetic computation technique comprises:

creating a new population of genomes;  
evaluating the population of genomes;  
evolving the population of genomes; and  
repeating evaluating and evolving the population at least until:  
a determination is made that there are no other results to be found;

a threshold is reached; or  
a user cancels generation of the genomes.

Claim 8. (Original) The method according to claim 7, wherein creating a new population comprises:

adding seeds to the population of genomes, the seeds comprising at least one of a forward bank order seed and a backward bank order seed; and  
filling the population with randomly created genomes.

Claim 9. (Original) The method according to claim 7, wherein creating a new population comprises:

seeding the population of genomes by building a forward bank order for a required number of banks;  
selectively storing a CRC value for the forward bank order for subsequent access;  
placing the forward bank order into the genomes;  
building a reverse order of banks;  
storing the CRC value for the reverse bank order; and  
placing the reverse order of banks into the genomes.

Claim 10. (Original) The method according to claim 7, wherein evaluating the population of genomes comprises testing for a best desired outcome.

Claim 11. (Original) The method according to claim 10, wherein evaluating the population of genomes further comprises at least one of determining weights for the genomes and determining an evaluation function adapted to be employed to compare and selectively order the genomes in the population.

Claim 12. (Original) The method according to claim 7, wherein evolving the population of genomes comprises:

mating parents to create at least one of crossover and mutated genomes; and  
filling the population of genomes with randomly created genomes.

Claim 13. (Original) The method according to claim 7, wherein, during the evolving of the population of genomes, two elite genomes are employed as parents for a new genome and a crossover technique is employed by the bank order determination unit after ensuring that both parents are not identical.

Claim 14. (Original) The method according to claim 13, wherein the parent genomes are mated by mixing respective parent genome bank order weights.

Claim 15. (Original) The method according to claim 7, wherein an elite genome and a non-elite genome are employed as parents for a new genome.

Claim 16. (Original) The method according to claim 7, wherein two genomes comprising at least one of elite and non-elite genomes are randomly selected as parents to create a new genome.

Claim 17. (Previously presented) A method of generating an update package for updating at least one of firmware and/or software in a mobile handset, the method comprising:

determining a bank order for updating the at least one of firmware and software in a bank-by-bank fashion, employing at least one genetic evolution technique;

determining values of parameters used for controlling generation of the update package; and

generating the update package, the update package incorporating the bank order.

Claim 18. (Previously presented) The method according to claim 17, wherein determining values for generation parameters employs the at least one genetic evolution technique.

Claim 19. (Original) The method according to claim 17, further comprising incorporating verification information in a generated update package facilitating integrity checking in a mobile handset receiving the generated update package.

Claim 20. (Original) The method according to claim 17, further comprising incorporating authentication information in a generated update package facilitating authentication of a source of the generated update package in a mobile handset receiving the generated update package.

Claim 21. (Original) The method according to claim 17, further comprising incorporating information in a generated update package facilitating fault tolerant update in a mobile handset receiving the generated update package.